



SPM020P

Multicrystalline Silicon Photovoltaic Module

FEATURE:

- TUV certification
- UL certification
- High power module using 6" Multicrystalline solar cell.
- Using low iron tempered glass, EVA laminate TPT backsheet.
- Anodize aluminum frame protected.
- 10 years limited warranty of 90% power output and 25 years limited warranty of 80% power output..
- 1200 pcs in 20' container, 2640 pcs in 40' container.(20 pcs in one carton)



Solartech Power, Inc
13811 Bentley Place, Cerritos, CA 90703
Tel:562-926-1089 Fax:562-926-1021
www.solartechpower.com
sales@solartechpower.com

ELECTRICAL CHARACTERISTICS				
	SPM020P	SPM018P		
Power at STC (Pm)	20W	18W		
Maximum power voltage (Vpm)	17.2V	16.5V		
Maximum power current (Ipm)	1.17A	1.10A		
Open circuit voltage (Voc)	21.7V	21.0V		
Short circuit current (Isc)	1.25A	1.1A		
Tolerance	±5%	±5%		
Module efficiency	10.0%	8.9%		
Maximum system voltage	1000V DC			
Standard test conditions	Temperature 25°C, Irradiance 1000W/m ² , AM=1.5			
Temperature coefficient	Isc: 0.06%/K	Voc: -0.36%/K	Pmax: -0.5%/K	

Specifications	
Cell	Multicrystalline silicon solar cell, (156mmx26mm)
No. of cell and connection	36 (4x9)
Dimension	560mmx360mmx18mm
Weight	2.5KG

AMBIENT CONDITIONS	
Operating Temperature	-40°C to +85°C
Storage Humidity	<90%

Output	
Type of output terminal	Junction box
Cable	Length 3000mm 20AWGx2C

